



COD	MOD	A cm	B cm	Kg	
29003	Q1	8,5	15	0,30	10
29004	Q2	11	19,5	0,65	
29005	Q3	14	26	1,20	



MAIN FEATURES

For welding work at 45° and 90° angles

For industrial use

2,5 mm thick steel sheet joined with threaded screws

Ferrite magnet protected with bakelite resistant to high temperatures

MATERIALS AND FINISHING

Ral 2002 orange Epoxy painted 1.5 mm thick sheet metal for Q1 and 2.55 mm thick for Q2 and Q3

Bakelite (insulating material unaffected by heat) interior and exterior metal protection

Permanent ferrite magnet:

Q1: 60-32/10mm

Q2: 80-40/12mm

Q3:100-60/15mm

Metric 4 end threaded screws for the bakelite protectors, 3 for Q1 and 5 for Q2 and Q3. Passing through completely and being end threaded holds the two sheet metal pieces tightly together for the tool's whole working life.

PACKING AND LABELLING

Individual PET blister packs

EAN- 13 code

How to use instructions on back of the blister card

Boxes of 10 pieces each

APPLICABLE RULE

Manufactured in Taiwan .

The articles are vigorously tested in our quality control department to ensure maximum product guarantee by carrying out all necessary tests

There is no applicable security rule

Industrias Piqueras works following quality standards ISO 9001 and ISO 14001

